

Technical Specifications

Specifications

Power Rating: 230 V, 50 Hz / 60 Hz Dimensions: 38 x 38 x 58.4 cm

Weight: 25 kg

Construction: 304-series stainless steel

& durable plastic

Spin Speed: 2850 RPM Motor: 1/3 horsepower Cycle Time: 8 seconds

Power Consumption: 1.60 watts per cycle Certifications: Conformité Européene & Saudi Standards, Metrology and Quality

Organization





Safety Features

Manual self-start and self-stop No exposed moving parts Built-in residual-current device (RCD)

Recommended Unit and Utilities Location Diagram Centerline of 3/8 inch [9.5 mm] hole locating upper center hole of Wall Mount Bracket $\frac{3}{8}$ inch [9.5 mm] diameter hole used to locate the upper center hole of the Wall Mount Bracket Top of Wall Sign is located 60 +/-1/16 inches [152.5 cm +/-10 5 inches [27 cm] 11 inches [27.9 cm] The upper center hole of the Wall 31 inches [8.9 cm] 3 inches [7.6 cm] 2 mm] above has to be located $38 + \frac{1}{16}$ inches [96.5 cm +/- 2 mm] above the floor. 4 inches [10.2 cm] floor and [17.8 cm] centered over the (open) Suggested location for Internal Connection to Customers' Waste Drain Lid as Suggested location shown 1 inch [2.5 cm] for Internal Connections of Customer's Power Source 35 inches [8.4 cm] Floor

Installation

Wall mounted via supplied Wall Mount Bracket Direct electrical connection to a 230 V, 50 Hz / 60 Hz, 13 Amp dedicated circuit

Water drainage to approved sanitary waste line or to floor drain

Operating Features

Easy to follow instructions

Manual self-start and stop via hand pressure

on the lid

Removes approximately 95% of a swimsuit's

water in 8 seconds

Uses no heat

Model	Configuration
EC5	230 V, 50 Hz / 60 Hz*

*Must specify hertz when ordering

